


ARGUS

Argus is our alternative to Stratos and Talos series if it is required to install a nice looking LED fixture especially in urban contest.



- Modern design with nice impact into urban locations.
- Tempered glass protecting LEDs and optics.
- Proprietary full cutoff optics:
 - High visual comfort for road users thanks to the low glare level
 - No light pollution
 - Maximum energy efficiency thanks to the targeted optics.
- Optional control systems:
 - 1-10V / DALI
 - Virtual midnight
 - Remote wireless control
 - Power-line communication
 - Lineswitch.



TECHNICAL DATA

LED type	LUMILEDS
Step MacAdam	5 (3 on request)
LED driver	Xitanium
Input voltage	230 VAC
Efficiency min. - max.	101 - 118 lm/W
L80 B10 F10**	>80.000 hrs
PF	>0.95
Housing	SUPERCAST ® aluminum
Glass	Tempered 5 mm
Colour temperature	3000 K - 4000 K - 5700 K
Colour rendering index	CRI >75
Degree of protection	IP66
Electrical insulation	Class I or II
Operating temperature	-40...+50 °C
Weight	7.5 kg

MODELS

	Total power [W]	Overall flux* [lm]	Optical flux [lm]
4M550	27	3017	3915
4M700	34	3683	4930
4M850	41	4367	5945
8M400	39	4608	5655
8M550	53	5949	7685
8M700	68	7240	9860
8M850	82	8567	11890
12M400	58	6781	8410
12M550	80	8787	11600
12M700	102	10748	14790
12M850	124	12593	17980

* With optics 57A
** Failure rate F10 including driver

OPTICS

15S	57A
23A	59A
49A	64A
52A	85A
56A	88A

Available other optics for special applications.

DIMENSIONS

[mm]

